



SS18 HD

revised: 4/24/09

CAMERAS & LENSES

- 11 Thomson LDK-8000 Worldcam Triax HD Cameras
- 12 Thomson LDK-8000 CCUs
- 4 *Wiring for additional CCUs, Sony or Thomson, Triax or Fiber*
- 6 Worldcam Super Expanders
- 6 Canon 86x Zoom Lenses
- 4 Canon 21x7.8 Lenses
- 1 Canon 11x4.7 Wide Angle Lens
- 6 Vinten Vector 70 Pan Heads with Matthews Tripods
- 5 Vinten Vision 20 HH Tripods & Panheads

PRODUCTION

- Grass Valley Kalypso Switcher 4 M/Es
- 144x144 HD / SDI Video Router
- Abekas DVEous MX Dual Twin HD DVE with CPL control
- 11 Wohler Pre-Listen Stations / 11 Telex KP32 Intercom Panels
- Harris Centrio Virtual Monitor Wall Processor

AUDIO

- Calrec Sigma Digital Audio Console
- 60 dual layer faders
- w/Bluefin DSP Processing
- 128 x 128 analog Audio Router
- 512 x 640 AES Router
- SRS Circle Surround Encoder and Decoder **Upon Request**
- 2 Dolby E Multi-channel Encoder & Decoder
- 2 Digidart E w/zip no bernoulli
- 1 HHB Dual Drive CD Burner
- Genelec Monitor Speakers, L-C-R-LS-RS-Subwoofer
- 2 Studio Technologies Stereo Synthesizers
- 4 DBX 160 Compressor Limiters

MICROPHONES

- 6 Sennheiser HMD-25-1 Announcer Headsets
- 6 Sennheiser MKH-70P Long Shotgun Microphones
- 6 Sennheiser MKH-416P Short Shotgun Microphones
- 10 Electrovoice 635a Hand Microphones
- 4 Electrovoice RE-16 Hand Microphones
- 4 Sony ECM-55b Lavalier Microphones
- 4 Sony ECM-77b Lavalier Microphones

GRAPHICS

Upon Request

DIMENSIONS

53' long x 13'6" high x 8'6" wide
76' long x 13'6" high x 17' wide - expanded with tractor
56' long x 13'6" high x 17' wide - expanded without tractor
Tractor# PA AE96947 / Trailer # PA PT8491L
Total Weight: 79,500 lbs

POWER REQUIREMENTS

208 volts, 3 phase, 200 amps

RECORDING & PLAYBACK

- 1 Digibeta VTR DVW-A500
- Wiring to support a total of 7 VTRs*
- 1 EVS XT2 Spot Box
- 4-channel JPEG
- 4 EVS XT2 Live Slo-Motion System
- 6 channel
- Sport Net HUB for EVS LSM & Spot Box
- EVS X-File 2 File Transfer System
- Wiring to support 7 EVS frames*
- 3 Lance Slo-Mo Controllers
- 4 DVD Burners
- Virtual Monitor Wall

COMMUNICATIONS

- Telex ADAM Matrix Intercom
- 96 square matrix
- TIF - Telephone Interface (4 lines)
- 12 Wet RTS TW PL Channels
- 16 IFB Channels
- 6 Gentner QKTs
- 12 RTS IFB Beltpacks
- 24 RTS BP-325 Dual Listen Beltpacks
- 8 RTS SPK-300 Biscuit Box User Stations
- 12 Beyer DT-108 Single Muff Headsets
- 12 Beyer DT-109 Dual Muff Headsets
- 6 Daltec Talent Talkback Boxes
- 8 Motorola Walkie Talkies with Base Station
- Lucent Partner II Phone System - 16 lines

SUPPORT EQUIPMENT

- SD Output of all sources, PGM, PST, M/Es &, TX
- 12 Sony Upconverters
- 4 Sony Color Correctors
- 14 GVG SD Down Converters
- 6 Cobalt HD Frame Syncs
- 4 For-A DCC 700 Color Correctors
- 1 Frequency Agile TV Demodulator
- 2 Direct TV HD DSS Receiver
- Time Code Reader / Generator

OUTBOARD MONITORS

- 10 9" Color Monitors

CABLE

- 8 Triax - 500 ft
- 8 Triax - 250 ft
- 8 Triax - 100 ft
- 0 500ft. DT-12 Audio Mult
- 10 250ft. DT-12 Audio Mult
- 5 100ft. DT-12 Audio Mult
- 5 125ft. 10-wire Coax Loom
- 2 125ft. 5-wire Coax Loom

- 150ft. Power Cable
- Assorted Single line Coax & XLR cables